
"APPROVED FOR RELEASE: Thursday, July 27, 2000 CIA-RDP86-00513R00041212



"APPROVED FOR RELEASE: Thursday, July 27, 2000 CIA-RDP86-00513R00041212

L 3655-66

ACCESSION NR: AT5024877

graphite, mercury), thus leading to excessive losses of electric energy, overheating of the contacts, and other complications, it is expedient to replace them with coatings of some at least equally corrogion-resistant but more electro-conducting compounds (of the carbide, boride) and nitride types). In this connection, the technique of deposition also matters. Research and development work on the selection of compounds assuring a minimal voltage drop, and on the optimal techniques of their deposition, is already in progress. This problem is particularly important to the chlorine industry, where, chlorine electrolysis involves a highly aggressive medium and where a still greater problem is that of developing an insoluble anode to replace the troublesome graphite anode. Research into new, more effective anode materials is in progress. Thus, Soviet scientists have started laboratory tests of specimens of different refractory materials resistant to aggressive media: the carbides of Ti; Zr; Cr; Mo; W, carbidized T; the borides of Ti, Zr, Cr, boronized Ti; the nitrides of Ti, Zr, Cr, nitrided Ti; and molybdenum silicide. These studies have not yet produced the desired results, but this is no reason for discontinuing them, as proved by the recent publication of two patents (loffe, A. F. Fizika poluprovodnikov, Moscow, Izd-vo AN SSSR, 1957; Beet, H. Canadian Patent No. 643672, 1962) pertaining to a corrosion-resistant electrode used as an anode in electrolysis and consisting of a metal (Ti, Cr, Nb)

Card 2/

"APPROVED FOR RELEASE: Thursday, July 27, 2000 CIA-RDP86-00513R00041212

CCESSION NR: AT5024877 or its alloy coated with an electroconducing metal nitride. Orig. art. has:										
Ciarman 1 to	hla					41	1.50			
cooremion. In	stitute of	Problems i	n Kateria	la Science	J AN U	krSSR (institu	it probl	CS	
terialovedeni EMITTED: 06A	An in PE	rssr)	ENCL:	00		UB CODE				Section of the sectio
)5		OTHER:	605	•		•		and the same of th	-
				•						A
	-				•		Ċ			f. who sales
	(a) (b)									
	• • • •									
	1 1 2 2 2 2 7 1									
Da	• • • • • •								7 6. (6.00)	
. 3/3		4	2.1							1

AUTHOR: Epik, A. P.; Bovkun. G. A.; Golubchik, I. V.; Sinitsina, L. P.

AUTHOR: Epik, A. P.; Bovkun. G. A.; Golubchik, I. V.; Sinitsina, L. P.

AUTHOR: AUTHOR: Epik, A. P.; Bovkun. G. A.; Golubchik, I. V.; Sinitsina, L. P.

TITLE: Certain properties of carbide and boride diffusion coatings on refractory metals

SOURCE: AN UkrSSR. Institut problem materialovedeniya. Diffuzionnyye pokrytiya na metallakh (Diffusion coatings on metals). Kiev, Naukova dumka, 1965, 127-142

TOPIC TAGS: metal diffusion plating, refractory metal, boride, carbide, 1 corrosion resistance, wear resistance, metal scaling

ABSTRACT: Since the physicochemical properties of the diffusion coatings of refractory metals still remain relatively uninvestigated, the authors investigated the scale resistance, wear resistance, and chemical resistance of the carbide and boride diffusion coatings on Til ZTY Mo? and W? as well as of the boride coatings of TiB2. The boride coatings on Ti, ZTY Mo? and W? as well as of the boride coatings of TiB2, NbB2, Mo2B + Mo2B2, and W2B + W3B2, and the carbide coatings, correspondingly, the phases TiC, ZTC, Mo2C, and W2C + WC. Tests of the scale resistance of Card 1/3

L 3656-66

ACCESSION NR: AT5024878

the carbides of these refractory metals at oxidation temperatures of 600-1000°C showed that their scale resistance increases in the following order

$$Mo_2C < WC < W_2C < VC < TiC < TaC(NbC) < 2rC$$

For the borides, this sequence is as follows

$$\mathtt{TiB}_2 > \mathtt{ZrB}_2 > \mathtt{NbB}_2 > \mathtt{TaB}_2 > \mathtt{W}_2\mathtt{B}_5$$

with the borides being generally more scale-resistant than the carbides. Wear-resistance tests, in their turn, based on friction against a rigidly affixed rotating piece of sandpaper, showed that the boridized specimens are more wear-resistant than the carbidized specimens, and that both types of specimens are many times more wear-resistant than the refractory base metal. Measurements of the microhardness of the diffusion coatings showed that it approximates the microhardness of the corresponding phases of the stoichiometric composition. Finally, chemical-resistance tests of the specimens, as based on the authors' tests of corrosion resistance in hydrochloric, sulfuric, nitric, and phosphoric acids, as

Card 2/3

L 3656-66 ACCESSION NR: AT5024878

well as in alkalis, showed that carbidized W is the most wear-resistant, as it virtually does not interact with nitric, sulfuric, and phosphoric acids, while it only weakly interacts with alkali solutions. Of the boronized specimens, boronized W and Mo are the most corrosion resistant. These investigations are only in their initial stage, and they will be continued. Crig. art. has: 2 figures, 5 tables.

ASSOCIATION: Institute of Problems in Materials Science, AN UkrSSR (Institut problem materialovedeniya, AN UkrSSR)

SUBMITTED: 06Aug65

ENCL: 00

SUB CODE: MM, IC, GC

NO REF SOV: 025

OTHER: 007

90

Card 3/3

ACC NET AM5001717

Monograph

UR

Samsonov, Grigoriy Valentinovich; Epik, Aleksey Pavloyich

Coatings from refractory compounds (Pokrytiya iz tugoplavikh soyedineniy) Moscow, Izd-vo "Metallurgiya", 1964. 107 p. 111us., biblio. Errata slip inserted. 3060 copies printed.

TOPIC TAGS: coating, metal coating, refractory compound, refractory compound coating

PURPOSE and COVERAGE: This book is intended for engineering personnel of machine-building, metallurgical chemical and other branches of industry. It may also be useful to designers and planners. It summarizes Soviet and non-Soviet information on coating metals, alloys and graphite with refractory compounds, protecting these materials against high-temperature oxidation, and increasing their hardness, refractory properties, and resistance to erosion and corrosion. Methods and procedures of obtaining protective coatings, such as simple and complex boride, carbide, nitride, and silicide phases, on refractory metals are reviewed. Examples of using coatings made of refractory compounds in various engineering fields are given, and the properties of these coatings are discussed.

Card 1/2

UD0621.793:669.018.4

```
ACC NR. AM5001717

TABLE OF CONTENTS:

Foreword -- 3

Ch. 1. Boride coatings'-- 5

Ch. 2. Carbide coatings -- 33

Ch. 3. Nitride coatings -- 42

Ch. 4. Silicide coatings -- 55

Ch. 5. Coatings on graphite -- 84

Ch. 6. Certain properties of refractory compounds -- 93

Bibliography -- 104

SUB CODE: 13/ SUBM DATE: 260ct63/ ORIG REF: 083/ OTH REF: 050/
```

EPIK, E. Y., SHVETS, Y. T., DYBAN, E. P., STRADOMSKIY, M. V.

"Experimental investigation of Flow Turbulence on Heat Transfer at Air Motion in Tubes."

Report submitted for the Conference on Heat and Mass Transfer, Minsk, BSSR, June 1961.

8/021/61/000/005/012/012 D215/D304

AUTHORS:

Shvets', I.T., Member of AS UkrSSR, Dyban, Ye.P., Stradoms'kyy, M.V., Rudkin, S.K., and Epik, E.Ya.

TITLE:

Investigating radial components of velocity pulsation

during the motion of air in short pipes

PERIODICAL: Akademiya nauk Ukrayins koyi RSR. Dopovidi, no. 5,

1961. 644 - 648

TEXT: The ratio of these pulsations to mean velocity is usually considered as degree of turbulence (the so-called Karman number) where $\sqrt{(w_r^{+2})}$ is the mean square value of the radial component of

velocity pulsation, wo the mean velocity of streaming, with respect to the cross section of the pipe. The experiments were made on a seamless, hydraulically smooth pipe with inner diameter of 51 and length of 4000 mm. To increase initial disturbances, special turbulizators were put before the pipe, in the form of perforated placard 1/3

8/021/61/000/005/012/012 D215/D304

Investigating radial components ...

tes and gratings having different diameters of openings and different coefficients β (ratio of free passage to toal area). Measurements of magnitude of the pulsations were made according to the thermoanemometric method with the aid of ETA-5A set of instruments. The sensitive element was a V-shaped pickup connected with two adjacent arms of the measuring bridge. Pulsations were measured at seven longitudinal sections of the pipe and at seven points within each section. The type of variation shown here was found to be valid for all turbulizators, without any exception, also for a stream of air in a pipe without artificial disturbances. It can be assumed that the part of the pipe where the radial component of velocity pulsation is variable, is the zone of hydrodynamical stabilization of the stream. The relative length of this zone depends on geometrical characteristics of the turbulizator. Practically only one turbulizator among those tested had corresponding zone of stabilization longer than 30 diameters. Two other turbulizators were intended for calming and are not considered. The value of Kr can be found, with possible error up to 10 %, from

Card 2/3

Investigating radial components ...

S/021/61/000/005/012/012 D215/D304

$$Kr_{ser} = \frac{210}{Re^{0.5}} \tag{2}$$

(Kr ser is the mean value of Kr with respect to cross section of the pipe). The absolute value of the radial component of pulsation is

$$\sqrt{{\rm W}_{\rm r}^{1/2}} = 6.45 \cdot 10^{-4} \, {\rm Re}^{0.5}$$
 (3)

The attempt to find an empirical formula for the radial component of pulsation with respect to the length of stabilization zone has failed. The authors find that the determination of the radial component of pulsation alone is insufficient for the characterization of the stream in the initial zone of the pipe. There are 3 figures.

ASSOCIATION: Instytut teploenerhetyky AN URSR (Institute of Heatpower Engineering, AS UkrSSR)

SUBMITTED: February 1, 1960

Card 3/3

25350 8/021/61/000/007/008/011 D205/D306

26.5200

AUTHORS:

Shvets', I.T., Member AS UkrSSR, Dyban, E.P., Stradoms'kyy, M.V., Rudkin, S.K., and Epik, E.Ya.

TITLE:

Effect of the level of initial disturbances or the heat exchange intensity during turbulent air flow in short pipes

PERIODICAL: Akademiya nauk Ukrayins'koyi RSR, Dopovidi, no. 7, 1961. 920 - 923

TEXT: In calculations involving short heat exchange surfaces it is essential to take into account the effect of the air stream initial turbulence on the value of heat exchange coefficients. The authors studied the effects of pipe lengths, stream conditions and that of initial disturbances level on heat exchange intensity in pipes less than 80 diameters long [Abstractor's note: This expression probably means the ratio: length/diameter]. The lower pipe partition was heated to 150°C by electricity. The temperature was measured by Card 1/5.

25350 S/021/61/000/007/008/011 D205/D306

Effect of the level ...

means of thermocouples and the air temperature with a specific device, also previously described. The criterial equation Nu = f(Re) as well as the obtained experimental data proves that the physical flow conditions along the pipe length have less effect on the Nu value than on the heat exchange coefficient (beyond the latter stabilization level). Therefore, in evaluating experimental data — the pipe length influence on the average values of heat exchange coefficient, as well as that of the distance of the examined pipe partition from the pipe mouth, (for local data), the coefficient Ee was used, which is the ratio of Nusselt's number for the given pipe part and that for part remote from the air entrance. Investigation of heat exchange intensity with turbulent flow, without artificial turbulizers, proved that this intensity might be expressed (for pipe partitions beyond the stabilization level) by the following equation: Nu = 0.018 Re^{0.8}, which is in agreement with the well known generalization. During that kind of air flow, a laminar flow zone existed for the whole range of the studied Re values (up to Re = 5.104). Behind that zone a transitory zone was observed,

Card 2/1

25350 S/021/61/000/007/008/011 D205/D306

Effect of the level ...

Card 3/5

the length of which is inversely proportional to Re values (Fig.1). This leads to corresponding changes in the local Nusselt's numbers. By graphs illustrating the changes of the coefficient Ee along the pipe length, the local Nu numbers as well as the average ones' can be calculated (as long as parameters on the tube entrance are constant). When artificial turbulence devices are used the air flow characteristics change, but the zone of initial artificial perturbations does not exceed 30 diameters of the pipe length, even for the most effective turbulizer. As a result of increased local heat exchange coefficient in the first pipe partition, their average values are increased along a large stretch of pipe length and are inversely proportional to Reynold's numbers; so the average increase of Nusselt's number with the most effective turbulizer (one opening 10 mm in diameter, $\beta \Rightarrow 0.038$) was observed on the pipe length equalling about 600 diameters when Re was equal to 5.10^4 , but on a length of 75 diameters only when Re = $1.5 \cdot 10^6$. It follows that for evaluation of heat exchange data in the entrance part of a pipe heated by an air flow with natural as well as artificial turbulence it is necessary to make a correction on the pipe length: Ee =

25350

Effect of the level ...

S/021/61/000/007/008/011 D205/D306

 $\mbox{Nu/Nu}_{\mbox{\sc Nu/Nu}_{\mbox{\sc Nu}_{\mbox{\sc Nu/Nu}_{\mbox{\sc Nu}_{\mbox{\sc Nu}_{\mbox{\sc Nu/Nu}_{\mbox{\sc Nu}_{\mbox{\sc Nu}_{\sc Nu}_{\mbox{\sc Nu}_{\mbox{\sc Nu}_{\mbox{\sc Nu}_{\sc N$

ASSOCIATION Institut teploenergetiki AN URSR (Institute of Thermo-energetics AS UkrSSR)

SUBMITTED: February 1, 1961

Card 4/5

DYBAN, Ye.P.; RUDKIN, S.K.; STRADOMSKIY, M.V.; SHVETS, I.T.; EPIK, E.Ya.

Investigation of the radial component of velocity pulsations in a turbulent air flow in relatively short tubes with different levels of initial perturbation. Inzh.-fiz.zhur. 4 no.11:3-9 N .'61.

(MIRA 14:10)

1. Institut teploenergetiki AN USSR, g. Kiyev. (Aerodynamics)

EPIK, I.P. [Öpik, I.P.], kand.tekhn.mauk

Heating surface fouling in boilers burning Estonian oil shale. Mek. sta. 29 no.2:24-29 F *58. (NIRA 11:3) (Boilers-Incrustations) (Oil shales)

SOV/112-59-5-8540

Translation from: Referativnyy zhurnal. Elektrotekhnika, 1959, Nr 5, p 21 (USSR)

AUTHOR: Epik, I. P. and Mikk, I. R.

TITLE: Mechanism of Formation of Solid Fly-Ash Deposits on Convective Heating

PERIODICAL: Izv. vyssh. uchebn. zavedeniy. Energetika, 1958, Nr 3, pp 58-64

ABSTRACT: Apart from ash slagging and cementation due to sweating of cold surfaces, there are two major types of deposits of fly ash on convective heating sunfaces: powdery deposits (on the tail tube parts, or at low gas rates on both front and tail parts) and solid deposits on the front tube parts. The powdery deposits assume definite size depending on the by-passing gas and are easily removable. The solid deposits, in burning Estonian shales, are observed in the 500-900°C gas zone; they consist of calcium sulfate, and require boiler shutdown for their removal. Depending on the gas velocity, the deposits can be broken down into three groups: (1) with a gas velocity under

Card 1/2

CIA-RDP86-00513R00041212(APPROVED FOR RELEASE: Thursday, July 27, 2000

SOV/112-59-5-8540

Mechanism of Formation of Solid Fly-Ash Deposits on Convective Heating Surfaces 6 m/sec, large quantities of powdery deposits occur; (2) with gas velocities of 6-20 m/sec, the ash wearing effect precludes powdery deposits on the front side; only chemically active particles forming solid stony materials are deposited there; (3) with gas velocity over 20 m/sec, no petrescence is formed because the ash wearing effect is so high that it precludes this type of deposit entirely. These factors influence the formation of petrescences: (1) chemical factors, gas velocity; (2) the nature of the stream boundary layer (gas flowing by longitudinally or transversely), the fractional composition and concentration of the fly ash. Thus, in the solid-deposit zone, the tubes with a transverse by-flowing are unreliable and must be replaced with a longitudinally by-flowing surface or with a surface having a low cross factor.

B.I.L.

Card 2/2

EPIK, I.P.

KPIK, I.P., kand.tekhn.nauk dots.

Heat resistance of solid flash deposits in pipes in connection with combined lateral-longitudinal washing. Isv.vys.ucheb.
sav.; energ. 2 no.8:71-74 Ag 159. (MIRA 13:2)

1. Tallinskiy politekhnicheskiy institut. Predstavlena kafedroy teploenergetiki.
(Boilers--Incrustations)

RATNIK, B.Ya., insh.

Calculating heat transfer of semiradiating screenlike heating surfaces. Isv.vys.ucheb.sav.; energ. 3 no.3: 63-70 Mr '60. (MIRA 13:3)

1. Tallinskiy politekhnicheskiy institut. Predstavlona knfedroy teploenergetiki.

(Heat---Radiation and absorption)

EPIK, Il'mar Paulovich [Opik, Ilmar]; ANSON, P., red.; VAKHTRE, I. [Vahtre, I.], tekhn. red.

[Effect of the mineral parts of oil shale on the working conditions of the boiler unit] Vliianie mineral noi chasti slantsev na usloviia raboty kotloagregata. Tallinn, Estonskoe gos. izd-vo, 1961. 248 p. (MIRA 15:3) (Boilers—Firing)

23753

104100

S/170/61/004/006/008/015 B129/B212

11.9300

AUTHORS:

Mikk, I. R., Epik, I. P.

TITLE:

Solution of various three-dimensional problems of radiant heat transfer by reducing them to two-dimensional problems

PERIODICAL:

Inzhenerno-fizicheskiy zhurnal, v. 4, no. 6, 1961, 90-100

TEXT: A method is brought to calculate the degree of blackness for radiating volumes of infinite cylindrical systems. Various of the results reported are used for the critical analysis of the approximation method, which is described here. In connection with the development of modern heat engineering many papers have been published, which deal with the heat transfer by radiation between a medium of high temperature and the bounding walls. A significant success has been gained in the research of the physical properties of radiating media and a number of experimental data has been obtained, which are necessary for calculations. Determining the degree of blackness of a radiating volume is quite a different problem: To the present it only has been possible to find the respective formulas

Card 1/8

23753

S/170/61/004/006/008/015 B129/B212

Solution of various ...

for two cases analytically (by integration); for the volume of a sphere by Nusselt (VDI, v. 70, n. 23, 1926) and for the radiation at the center of a cylinder base by Schmidt (VDI, v. 77, n. 43, 1933). The generally known equation of the plane parallel layer is only a special case of the above formulas. So far, all other attempts to calculate the degree of blackness lead to a numerical or graphical integration of the initial expressions. Therefore, the approximate method of determining the degree of blackness of a medium, which is based on reducing the three dimensional to twodimensional problems is now widely employed. It makes it possible to express the degree of blackness by an exponential function. The simplicity of the formulas obtained is very advantageous, but the "effective layer thickness" has to be considered, which is a completely conditional quantity. Since the rules for the selection of the latter are only based on the above two expressions and some results of the numerical integration it is impossible to check the correctness of the calculated results or the estimation of the probable error for other cases. This article tries to close this gap by pointing to the analytical method of solving problems for infinitely long cylindrical systems. The author brings an analytical

Card 2/8

23753 S/170/61/004/006/008/015 B129/B212

Solution of various...

method or reducing a three-dimensional problem into a two dimensional one in order to determine the degree of blackness for radiating volumes of infinitely long cylindrical systems. The following assumptions are made: 1) The system investigated corresponds to that of Fig. 1; 2) the medium between the areas F_1 and F_2 will radiate onto the element dF_1 ; 3) the medium is isothermal and homogeneous; 4) monochromatic or gray emission takes place according the Buger law. The reduction to the two-dimensional

problem is done through the integral

olem is done through the integral
$$\frac{\pi/2}{\mu} = \int_{-\pi/2}^{+\pi/2} \exp(-k\eta/\cos^2\theta) \cos^2\theta d\theta = 2 \int_{0}^{\pi/2} \exp(-k\eta/\cos^2\theta) \cos^2\theta d\theta.$$

It is shown that the heat transfer problem ends up in the integration of

$$J = \int_{-\pi/2}^{\pi/2} H(f) \cos y dy (9), \text{ where } f = k \eta \text{. Integrating (9) determines } f$$

Card 3/8

23753 S/170/61/004/006/008/015 B129/B212

Solution of various...

as function of φ . For $\eta=R=$ const the following expression holds for the degree of blackness: $\xi=1-\frac{2}{\pi}$ M(kR). The degrees of blackness are determined for simple geometrical systems (Fig. 5). The results are compiled in Table 2. There are 5 figures, 2 tables, and 8 references: 5 Soviet-bloc and 3 non-Soviet-bloc.

ASSOCIATION: Politekhnicheskiy institut Tallin (Polytechnical Institute

SUBMITTED: February 8, 1960

Card 4/8

EPIK, I.P., kand.tekhn.nauk; REZNIK, V.I., inzh.

Selecting the thermal circuit and component layout of high-capacity boiler units fired with Estonian shale taking into account the characteristics of the mineral part of the fuel. Energomashinostrocnie 7 no.12:5-9 D '61. (MIRA 14:12) (Boilers-Design and construction) (Estonia-Shale)

EPIK, I.P., kand.tekhn.nauk; OTS, A.A., kand.tekhn.nauk; HIKK, I.R., kand.-

Distribution of the burner radiation intensity through the width of the furnace walls. Teploenergetika 8 no.12:43-45 D '61. (MIRA 14:12)

1. Tallinskiy politekhnicheskiy institut. (Boilers)

EPIK, I.P., kand.tekhn.nauk, dotsent; OTS, A.A., kand.tekhn.nauk, dotsent

Clogging factor of a furnace operating on pulverized shale. Izv.vys.ucheb.zav.; energ. 5 no. 8:50-55 Ag '62. (MIRA 17:7)

1. Tallinskiy politekhnicheskiy institut. Predstavlena kafedroy teploenergetiki.

EPIK, I. P., kand. tekhn. nauk; OTS, A. A., kand. tekhn. nauk

Distribution of the intensity of the radiation of a torch along the height of furnace walls. Teploenergetika 10 no.3: 51-53 Mr 163.

1. Tallinskiy politekhnicheskiy institut.

(Boilers) (Heat-Transmission)

EPIK, I. [Opik, I.], kand. tekhn. nauk; OTS, A., kand. tekhn. nauk

Measuring the radiation intensity of a flame with radiometers designed for nonsteady-state thermal conditions [with summary in English]. Izv. AN Est. SSR, Ser. fiz.-mat. i tekh. nauk 12 no.1:75-80 163. (MIRA 16:5)

l. Tallinn Polytechnical Institutes (Radiometry)



"APPROVED FOR RELEASE: Thursday, July 27, 2000 CIA-RDP86-00513R00041212





EPIK, I.P., doktor tekhm. nauk, prof.; TAAL, Kh.P., inzh. [Taal, H.]

Study of the volatilization of shale ash in a reducing medium at high temperatures. Izv. vys. ucheb. zav.; energ. 7 no.6270-75 Je *64

1. Tallinskiy politekhmicheskiy institut. Predstavlona kafedrpy teploemergetiki.

"APPROVED FOR RELEASE: Thursday, July 27, 2000

CIA-RDP86-00513R00041212

JD/WB/GD-2 IJP(c) EWT'm)/EWP(t)/ETI SOURCE CODE: UR/0114/66/000/003/0034/0035 39693-66 ACC NR. AP6009727 AUTHOR: Epik, I. P. (Doctor of technical sciences, Professor); Tomann, E. L. (Engineer) ORG: none TITLE: Corrosion of 1kh18N9T steel in air and in flue gases in the presence of shale ashes SOURCE: Energomashinostroyeniye, no. 3, 1966, 34-35 TOPIC TAGS: steel corrosion, gas corrosion ABSTRACT: The required test atmosphere was produced in a laboratory by burning shale domestic gas with an admixture of sulfur dioxide and air. These findings are reported: (1) The IKh18N9T steel in air at temperatures below 650C practically does not suffer corrosion; (2) In the above flue-gas atmosphere, the corrosion is very low (at 600C, the corrosion loss was 6.1 g/ms after 120 hrs); (3) The corrosion loss of the steel in the flue gases equals that of steel plates buried in shale ashes in the presence of air. Orig. art. has: I figure. SUB CODE: 11, 13 / SUBM DATE: none / ORIG REF: 002 UDC: 620.193.5:669.15 Card 1/1 9d

S/021/62/000/006/013/013 D251/D308

AUTHOR:

Epik, O.P.

TITLE:

First seminar in the Viddil technichnyth nauk AN URSR (Department of Technical Sciences of the AS UKrSSR) on the surface diffusion saturation of metals and coatings of refractory compounds on metals and non-metals

PERIODICAL:

Akademiya nauk Ukrayins'koyi RSR. Dopovidi, no. 6, 1962, 837 - 839

TEXT: This is an account of the first seminar on surface diffusion saturation of metals and coatings of refractory substances on metals and non-metals. The seminar was organized by the VTW of the AS UkrSSR and the Odes'kyy politekhnichnyy instytut (Odessa Polytechnic Institute) and held in Kiyev, March 22-23, 1962. Nore than 80 specialists from all parts of the USSR took part. The opening speech, devoted to general aspects of the problem, was given by H.V. Samsonov, Head of the VTN AS UkrSSR and Corresponding Nember of the Academy. H.V. Zemskov (Odessa Polytechnic Institute) read two papers

Card 1/3

S/021/62/000/006/013/013

First seminar in the Viddil technichnykh. D251/D308

on methods of intensifying chemico-thermal processes with the use of high-frequency currents and also on a proposed series of experiments on multi-component diffusion on alloy surfaces. H.M. Dubinin of the Moskovs'kyy aviatsiynyy instytut (Moscow Aviation Institute) spoke on complex alloying using a base of molybdenum and niobium and the study of the remaining stress which is induced by the saturation of metal alloy surfaces. Yu.M. Hryboyedov of the Tsentral'nyy naukovodoslidnyy instytut tekhniolohiyi mashynobuduvannya (Central Scientific Research Institute of Machine Construction Technology), Moscow, spoke on nitrification processes. O.P. Epik of the Instytut metalo-keramiky i spetssplaviv AN URSR (Institute of Metal Ceramics and Special Alloys of the AS UkrSSR) made a study of the diffusion parameters in the borification and carbonification of solid-phase tungsten and molybdenum. V.M. Konyev of the Ural's'kiy universytet (Ural State University) in Sverdlovs'k, spoke on the work of his university in the field of diffusion coatings on metals. L.V. Strashyns'ka of the Institute of Metal Ceramics and Special Alloys of the AS UkrSSR spoke of contact interactions in the solid phase at high temperatures. O.Ya. Artamonov of the same Institute spoke of electroerosive cleansing processes for solid surfaces. I.M. Rovyns'kyy of Card 2/3

S/021/62/000/006/013/013

First seminar in the Viddil technichnykh..D251/D308

the Doslidnyy zavod derzhplanu URSR (Research Plant of the State Plan of the UkrSSR) spoke on the thermochemical processing of steel and alloys in liquid high-temperature electrolytes. M.H. Kaydash of the Odessa Polytechnic Institute spoke on the borification of steel under a vacuum in a solid-phase bath. Each paper was followed by a discussion. The importance of continuing such seminars and of carrying out deeper experimental and theoretical research in this field and of arranging a greater dissemination and interchange of results between researchers was stressed.

Card 3/3

ACCESSION NRT AP4010060

5/0021/64/000/001/0067/0070

AUTHOR: Samsonov, G. V. (Corresponding member); Epik, O. P.

TITLE: The reactive diffusion of boron and carbon in refractory transition metals

SOURCE: AN UKTRSR. Dopovidi. no. 1, 1964, 67-70

TOPIC TACS: transition metal, diffusion, refractory, reactive diffusion, phase composition, carbide, boride, activation energy, diffusion parameter, quantum number, Ti, Zr, Nb, Ta, No, W, C, B, physical metallurgy

ABSTRACT: This paper deals with an investigation of the effect of the conditions of boration and carbidization of titanium, zirconium, molybdenum and tungsten and of boration of niobium and tantalum on the structure, phase composition and thickness of diffusive carbide and boride coatings. The diffusion parameters of boron and carbon in those metals were determined by the results of metallographic, x-ray and chemical investigations, as well as by measurements of the thickness and microhardness of the diffusion layers. The previously established dependence between the criterion of acceptor capacity of the d-electron shell of metal atoms $1/N_{\rm n}$ (n is the number of electrons in the d-shell. N the principal quantum number)

Card 1/2

ACCESSION NR: AP4010060

and the magnitude of the activation energy is confirmed. Orig. art. has 3 figures and 2 tables.

ASSOCIATION: Insty*tut metalokeramiky* 1 spetssplaviv AN UkrRSR (Institute of Metal Ceramics and Special Alloys, AN UkrRSR)

SURVITTED: 19Apr63

DATE ACQ: 10Feb64


ENCL: 00


SUB CODE: ML, PH


NO REF SOV: 010


OTHER: 000

Card 2/2









EPIK, P. A.

Epik, P. A. and Orochico, A. I. "The solubility of mercury sulfide in promides and shlorides," Izvestiya klyevsk-politekhn. in-ta, Vol VIII, 1948 (on cover: 1910), p. 167

SO: U-52hl, 17 December 1953, (Letopis 'Zhurnal 'nykh STatey, No. 2a, 1919)

EPIK, P. A.


Epik, P. A. and Tolstikov, V. P. "The effect of pH-characteristic of the media on the oxidation reaction of sulfites by chlorates," Izvestiya Kiyevsk. politekhn. in-ta, Vol. III, 1948 (on cover 1949), p. 168-69

SO: U-52h1, 17 December 1953, (Letopis 'shurnal 'nykh Statey, No. 26, 1949)

EPIK, P. A.

Epik, P. A. "Chemical equilibrium constants of some complex reaction" Izvestiya Kiyevsk. politekhn. in-ta, Vol VIII, 1948 (on cover: 1949), p. 170-71

SO: U-5241, December 1953, (Letopis 'Zhurnal 'nykh Statey, No. 26, 1949)



"APPROVED FOR RELEASE: Thursday, July 27, 2000

CIA-RDP86-00513R00041212

EFIC, F.A.

USSR/ Chemistry - Oxidation reaction

Card 1/1

Pub. 22 - 27/54

Authors

1 Epik. P. A., and Shub. N. S.

Title

Frontal course of arsenite oxidation reaction with iodate

Periodical : Dok. AN SSSR 100/3, 503-506, Jan 21, 1955

abstract

: Experimental data are presented regarding the frontal course, mechanism, autocatalysis and origin of the arsenite oxidation reaction with iodate. In the part of the solution through which the reaction front has already passed the oxidation reaction was observed to continue until its termination and was very insignificant in the remaining parts. When the reaction front originates elsewhere than on the surface of the solution it was seen suddenly shifted upwards (in the reactor) with a speed of 80-169 mm/min Four USSR references (1906-1952). Illustrations.

Institution : The Polytechnicum, Kiev

Presented by : Academician A. N. Frunkin, November 23, 1954

Hew method for determining iodate and bromate from their mixture.

Inv. HPI 20:90-94 '57.

(Iodates) (Bromates)

EPIK, P.A., dots., kand.khim.nauk; SHUB, N.S., kand.khim.nauk

Iodine determination in the presence of bromides and chlorides.

Isv. EPI 20:95-99 '57.

(Iodides) (Bromides) (Chlorides)

(HIRA 11:3)

Frontal reaction pattern of sulfite iodate oxidation. Izv. KPI

20:100-107 '57.
(Sulfites) (Oxidation) (Iodates)

AUTHORS:

Epik, P. A., Orochko, A. I.

SOV/78-3-8-23/48

TITLE:

The Dependence of the Stability of Some Oxygen Containing Inorganic Compounds on the pH-Value of the Medium (Zavisimost; ustoychivosti nekotorykh kislorodsoderzhashchikhneorganicheskikn

soyedineniy ot pH sredy)

PERIODICAL:

Zhurnal neorganicheskoy khimii, 1958, Vol. 3, Nr 8, pp. 1855-

1864 (USSR)

ABSTRACT:

The resistance of the oxidizing agents KClO₃, KBrO₃, KJO₃, K $_2$ Cr $_2$ O₇, KMnO $_4$, NaClO $_2$ and NaClO to the action of sulfuric acid in aqueous solution was investigated. The results show that on certain conditions some of these oxygen containing oxidizing agents completely decompose, and that others in the same case remain unchanged. The deformation and decomposition of the oxygen containing oxidizing agents is due to the catalysis of hydrogen ions. The decomposition rate of KMnO $_4$ in acid medium increases

with the increase of the acid concentration. The decomposition rate of potassium permanganate does not take place monotonously.

Card 1/3

With the increase of the normality of the acid to 23 N the de-

507/78-3-8-23/48

The Dependence of the Stability of Some Oxygen Containing Inorganic Compounds on the pH-Value of the Medium

composition rate increases, on a further increase of the concentration to 30 N it decreases, and on another increase of the concentration it increases again. The investigation of the stability of potassium bichromate shows that the decomposition of this oxidizing agent under the action of sulfuric acid takes place according to the following equation:

 $2Cr_2O_7^{24} + 16 H^+ = 4 Cr^{3+} + 3 O_2^- + 0 H_2O$

The decomposition rate of this reaction was investigated in 16,5-, 19,8-, 23,1- and 33,2 N-sulfuric acid solutions. The results obtained show that at room temperature potassium bi-chromate is relatively resistant to the action of sulfuric acid. The stability of the oxidizing agents at boiling temperatures was investigated. The oxygen containing oxidizing agents with regard to their resistance to sulfuric acid must be classified as follows: KJO₃, K₂Cr₂O₇, KClO₃, KErO₃, NaClO and NaClO₂. Potassium permanganate does not take any fixed place among these oxidizing agents.

Card 2/3

SOV/78-3-8-23/48

The Dependence of the Stability of Some Oxygen Containing Inorganic Compounds on the pH-Value of the Medium

Based on the results obtained on the resistance of the oxidizing agents mentioned above to the action of sulfuric acid the qualitative analysis of certain mixtures of these oxidizing agents

can be carried out.

There are 9 figures and 22 references, 17 of which are Soviet.

ASSOCIATION:

Kiyevskiy politekhnicheskiy institut (Kiyev Polytechnical

Institute)

SUBMITTED:

July 8, 1957

Card 3/3

AUTHORS:

Epik, P.A., Orochko, A.I.

32-24-4-12/67

TITLE:

The Determination of Chlorites and Hypochlorites in Their Mixture (Opredeleniye khloritov i gipokhloritov v ikh smesi)

PERIODICAL:

Zavodskaya Laboratoriya, 1958, Vol. 24, Nr 4, pp. 413-415 (USSR)

ABSTRACT:

As determinations with arsenic- and platinum preparations cause certain difficulties, the endeavor was made to find other reducing substances for these investigations. Experiments were made with bivalent cations of cobalt, nickel, and manganese, as well as with hydrogen peroxide, in which mixtures of pure chlorite and hypochlorite were used as 0.1 - 0.2m solutions. Experimental results for cobalt (II) and nickel (II) ions showed that they are unsuited for the required determination. When evaluating the influence exercised by the alkaline medium upon the course of the reduction of hypochlorite by manganese (II) it was found that the interval 8.2 < pH < 10.2 must be considered an optimum for the reduction of hypochlorite beside chlorite. Hydrogen peroxide was used with an alkalinity of 0.2 - 0.5m lye, which was found to be

Card 1/2

The Determination of Chlorites and Hypochlorites in Their Mixture

32-24-4-12/67

an optimum. As a buffer solution in the case of manganese (II) sodium bicarbonate or Na₂HPO₁, was used, but the latter slowed down filtration. The suggested volumetric methods of determination can also be used for separating chlorite from hypochlorite and for a quality reaction on chlorite beside hypochlorite. There are 2 figures, 2 tables, and 2 references, 2 of which are Soviet.

ASSOCIATION:

Kiyevskiy politekhnicheskiy institut (Kiyev Polytechnic Institute)

- 1. Chlorates--Determination 2. Cobalt ions--Chemical effects
- 3. Nickel ions--Chemical effects 4. Hydrogen peroxide

-- Chemical effects

Card 2/2

5.3200 5.3200

Epik, P. A., Tolstikov, V. P.

67032

SOV/153-2-5-5/31

TITLE:

AUTHORS:

Selective Iodometric Determination of Oxidizers

PERIODICAL:

Izvestiya vysshikh uchebnykh zavedeniy. Khimiya i khimicheskaya tekhnologiya, 1959, Vol 2, Nr 5, pp 667-673 (USSR)

ABSTRACT:

The rate and conversion degree of many redox reactions can be influenced at a high degree, or even prevented, by adjustment of the pH-values. As the corresponding zones of the pH-values of different reactions can be distinguished, the oxidizers can often be determined by selectivity. To establish these new methods of determination, a systematic study of the dependence of kinetics of many redox reactions on the pH becomes necessary. The authors carried out the study of the oxidation of the iodide (Ref 6). The present paper reports on a similar study in which arsenite was used as a reducing agent. The data published by various researchers on the dependence of the oxidation of the arsenite on the pH-value (Refs 4, 8-16), are difficult to compare. The authors wanted to study this dependence by applying various oxidizers. This is necessary - while the other conditions are constant - for the elaboration of the arsenite-

Card 1/3

APPROVED FOR RELEASE: Thursday, July 27, 2000 CIA-RDP86-00513R000412120

iodometric determination of several of these oxidizers.

Selective Iodometric Determination of Oxidizers

67032 SOV/153-2-5-5/31

Arsenite can be rapidly and accurately titrated at 7 < pH < 11. Figure 1 lists materials used as buffer solutions for keeping the above pH-range. 18 oxidizers were studied: nitrite, nitrate, vanadate, arsenate, antimonate, selenite, selenate, tellurite, tellurate, molybdate, chlorate, bichromate, hypochlorite, chlorite, bromate, iodate, periodate and permanganate. The experiment showed that the first 11 of the listed oxidizers were practically not reduced by the arsenite in the pH-range between 0 and 14 within the first 10 minutes. Permanganate is reducible at practically all pH-values, but no reproducible results were obtained. In each case a mixture of manganese compounds is being formed, each having a different valency. Tables 2 and 3 show that the remaining oxidizers react with arsenite depending on the pH and At (time elapsed between preparation of the reaction mixture and the start of the titration). Subsequently, several peculiarities of these reactions are mentioned. Table 3 gives the results of the determination of periodate. A figure (p 671) illustrates all of the results. The selective determination of several oxidizers containing oxygen is dealt with separately. Table 4 shows the determination of chromate in the presence of

Card 2/3

67032

Selective Iodometric Determination of Cxidizers

SOV/153-2-5-5/31

arsenate, antimonate and selenite; table 5 the determination of hypochlorite. The results give a review of the possibility of carrying out the determination mentioned in the title, and the conditions necessary for this. The practicability of the following selective iodometric determinations was confirmed: of chromate in the presence of arsenate, antimonate, selenite and molybdate (used separately); of hypochlorite in the presence of chromate; of bromate in the presence of vanidate. In most of the binary mixtures of oxidizers, both oxidizers can be determined by additional titration if the acidity of the medium is correct. There are 1 figure, 5 tables, and 18 references, 10 of which are Soviet.

ASSOCIATION:

Kiyevskiy politekhnicheskiy institut; Kafedra analiticheskoy khimii (Kiyev Polytechnic Institute, Chair of Analytical Chemistry)

SUBMITTED:

June 21, 1958

Card 3/3

EPIK, P. A.; PERCHIK, F. I.

Oxidation reactions of ferrocyanide by some oxidizing agents as dependent on pH of the medium. Izv. vys. ucheb. zav.; khim. i khim. tekh. 5 no.5:703-708 62. (MIRA 16:1)

1. Kiyevskiy politekhnicheskiy institut, kafedra analiticheskoy khimii.

(Ferrocyanides) (Oxidation) (Hydrogen-ion concentration)

KONKIN, Vasiliy Dmitriyevich; ZHIKHAREVA, Valentina Iosifovna; EPIK, P.A., kand. tekhn. nauk, retsenzent;

[Complexometric analysis] Kompleksometricheskii analiz. Izd.2., perer. i dop. Kiev, "Tekhnika," 1964. 255 p. (MIRA 17:6)

EPIK, P.A.; TOLSTIKOV, V.P.

Frontal progress of the oxidation reaction of sulfite with chlorate. Zhur. fiz. khim. 39 no.4:947-950 Ap '65.

(MIRA 19:1)

1. Kiyevskiy politekhnicheskiy institut. Submitted Dec. 14, 1963.

DAVTYAN, O.K.; Prinimali uchastiye: EPIMAKHOV, Yu.K.; MISYUK, E.G.; BURSHTEYN, I.I.; SEMIZOROVA, N.F.

Mechanism of oxidation, hydrogenation, and electrochemical combustion on solid catalysts. Part 12. Zhur. fiz. khim. 39 no.4:877-883 Ap '65. (MIRA 19:1)

1. Odesskiy gosudarstvennyy universitet imeni Mechnikova. Submitted Aug. 17, 1963.

MPISKOPOSOV, G. L.

"Atomic sociology" is an ideological weapon of American imperialism. Moskva, Gos. izd-yo polit. lit-ry. 1953. 108 p. (54-35432

1744.16

RAGO, Gerhard, prof.; EPLER, H., spets. red.; TOMING, R., red.; KOHU, H., tekhm. red.

[Higher mathematics] Korgem matemaatika. Tallinn, Eesti riiklik kirjastus. Vol.1. 1962. 738 p. (MIRA 15:5)

1. Tartu University (for Rago).
(Mathematics)

R. Epler, "Macterial Marfare," Polska Gaz, Lok., 14: 203-5, 1935.

"APPROVED FOR RELEASE: Thursday, July 27, 2000


CIA-RDP86-00513R00041212

EL'PINER, I. Ye. SHEYNKER, A. P.

"Production of Endotoxin (Of the Culture of bacillus pertussis) by Ultrasonic Waves,"

Byull. eksp. biol. 1 med., 1947, 7, 51

M-28, 14 Dec 1954




The Polarigraphy Biology

"The Polarigraphic Method in Biology and Medicine,"
I. E. Elpiner, 20 pp

"Uspek Sovremen Biolog" Vol XXIII, No 2


Gives 1) description of method, 2) polarigraphic analysis of inorganic substances in biologic tissues,
3) polarigraphic maximums, 4) polarigraphic analysis of biologically active organic substances, 5) polarigraphic catalytic protein waves, 6) catalytic protein waves and symptoms of cancer.



HERR /Medicine - Sounds Wedicine - Therapeutice Riphens nature of supersonic waves and methods of producing them. Discusses cavitation phenomena. Discusses of cavitation. Mentions secondary factors-pressure gradient and heat; considers that sain blacked action of ultrasonic waves that such chemical articles as depolymentation. Mentions secondary factors-pressure gradient and heat; considers that sain blacked action of ultrasonic waves that sain phenomena. Discusses a component of protopless. Contest in B. Barakly's views on this subject. Description of albuminous component of protopless. Centest in B. Barakly's views on this subject. Description of all trasonic waves. Tis the article of the applications of alternation of indian under the action of fultrasonic waves," public in Discussions of article of the said of the Said article of the Said	ELPINER, I. Ye.	PA 3/49T59	%
	plains nature of supersonic vaves and methods producing them. Discusses cavitation phenomens scribes destruction of tissue cells and bacterisepote supersonic waves. Shows that such chemical rects as depolymentiation. Hentions secondary factor essure gradient and heat; considers that sain clogical action of ultrasonic waves is due to 3/49759 ER/Kedicine - Sounds (Contd) REP/Kedicine - Sounds (Contd) REP/Kedicine - Sounds (Contd) REP/Kedicine of albuminous component of protoplass otes I. B. Barskiy's views on this subject. Intions various therapeutic applications of trasonic waves. The article of the applications of trasonic waves. Is the article of the and Reduction of Land of the action of the sonic waves," public learning the action of the sonic waves, "public learning the action of the sonic waves," public learning the action of the sonic waves, "public learning the action of the sonic waves," public learning the action of the sonic waves, "public learning the action of the sonic waves," public learning the sonic waves, "public learning the sonic waves," public learning the sonic waves, "public learning the sonic waves and the sonic learning the sonic waves and th	Medicine - Sounds Medicine - Therepeutics ersenic Waves in Biology and Medicine, " I. ner, Moscow, 24 pp ekhi Sovrem Biol" Vol XXV, No 2	The second of th


EL'PINER, I. Ye.


"Problem of Variations in Albumin Structure in Cancer," Arkhiv Patol., 11 No 3, 1949. Lab of Biochemistry of Cancer, Acad, Med Sci USSR, Moscow, 1949



Mew theory on the biological effect of ultrasonic waves.
Usp. soverm. biol. 30 no.1:113-129 July-Aug. 1950. (CIML 20:1)

1. Moscow.





EL'PINER, I. E.

"Physico-Chemical and Biological Action of Ultrasonics," a paper presented at the conference of the Acoustics Cormission NS USSR held in Leniugrad 1-3 Feb 51.

W-21610, 25 Feb 52

PA 19324

ELPTHER, I. YE.

USER/Biology - Ultrasonics


Oct 51


"Biological and Chemical Processes in Ultrasonic Fields, I. Ye. Elpiner

"Zhur Tekh Fiz" Vol XXI, No 10, pp 1205-1212

Author refers to his previous works (cf. "Uspekh Sovrem Biol", 25 (1948) and 30 (1950)). He describes destructive effect of ultrasonics on disease-carrying bacteria and the splitting by ultrasonics of high-mol protein structures and organic mols; explains the mechanism governing the chem effect. Submitted 31 Dec 50.

19374





PINER, Being translated Waren 1953	to the appearance of pyrroles, but no noticeable formation of bile pigments could be observed. It is concluded that the iron atom apparently plays the role of a factor which creates a high deg of stability of the porphyrin nucleus. Data obtained can be used for evaluating effect of oxygen: in E2 atm, splitting of porphyrin by ultrasound does not occur.	"Dok Ak Nauk SSSR" Vol LXXIX, No 3, pp 495-497 Under action of ultrasonic waves in air the splitting of hemin is slow. With sufficiently powerful ultrasonic waves, the breaking up of hemin proceeds up		UBSR/Chemistry - Blood; Effects of 21 Jul 51 Ultrasound	The provide the second of the
-------------------------------------	--	--	--	---	---

GINZEURG, H. M.; YELIPIN R. I. Ye.

Gums - Diseases

Polarographic study of salivary proteins of the parotid gland in alveolar pyorrhem., Stomatologiia, no. 1, 1952.

9. Monthly List of Russian Accessions, Library of Congress, May 1953, Unclassified

EL'PINER, I. Ye.

USBR/Biology, Medicine - Microbiology Mar/Apr 52

"Ultra-Sound Waves in Microbiology," I. Ye. El'piner

"Mikrobiol" Vol XXI, No 2, pp 228-238

Reviews USSR and foreign work on the subject, listing 30 Russian and 24 foreign references. Giving as an example his own work on the isolation of whooping cough endotoxin, discusses isolation of biologically active substances (toxins, endotoxins, antigens, etc.) from bacterial cells with the aid of ultra-sound.

210718

Translation M-646

BL'PINER, I.


Biologic effect of ionizing radiation. Usp. sovrem. biol. 34 no.2:219-243 Sept-Oct 1952. (CLML 25:5)

1. Moscow.

EL'PINER, I. Ye.

"USSR Work on Application of Ultrasound Waves in Biology," Priroda, 41, No.11, pp 109-114, 1952

Translation W-27751, 10 Sep 53



EL'PINER, I. YE. to ultrasound. poments of nucleic acids, which are very sensitive investigated. The bases in question are comaction of ultrasound also protect the bases selves (leucine, methionine, etc.) under the sent there which result from the splitting of water mols. Some amino acids which decomp themthe quantity of chemically active radicals prespaces formed by cavitation, thus reducing planation is that the org solvents evap into the by these substances on methylene blue. hibited. uracil, by ultrasound was almost completely inethyl ale or methyl alewas addecte an ag soln contg than adenine or guan 'me. When ethyl ether, Uracil proved to be more sensitive to ultrasound "Dok Ak Nauk SSSR" Vol LXXXII, No 4, pp 611-614 Lab of Biochem of Cancer, Acad Med Sci USSR Pyrimidine Bases," I. Yo. El'piner, Ts. B. Kays, "The Effect of Ultrasound Waves On Purine and USSR/Chemistry - Medicine, Ultrasound The same protective effect was exerted M-28 14 Dec J4 The ex-1 Feb 52

APPROVED FOR RELEASE: Thursday, July 27, 2000


CIA-RDP86-00513R00041212(

ELIPINER, I.Ye.; GERASINOVA, A.V.

Effect of ultrasonics on depolymerase of desoxyribonucleic acid.

Doklady Akas. namk 86 no. 4:797-800 1 Oct 1952. (GLML 23:3)

1. Presented by Academician A. I. Oparin 5 September 1952. 2. Academy of Medical Sciences USSR.





EL'PINER, I. (2.

"The Biological Action of Ultrasonic Waves"

Zhur Obsh Biologii, Vol XV, No 1, 1954 pp 18-30

Trans.

M-28, 14 Dec 54

USSR/Biology - Biochemistry

Cord

: 1/1

Authors

Oparin, A. I. Academician; Gel'man, N. S. and El'piner, I. E.

EL PINER, L

USSR/Physics - Biophysics

Pub. 22 - 15/40 Oard 1/1

Authors

: El'piner, I. E., and Surova, M. D.

Title

Acceleration of albumen decomposition processes in the field of ultrasonic waves -

Periodical : Dok. AN SSSR 99/2, 243-246, Nov 11, 1954

Abstract : Experiments show that the decomposition of albumen molecules, observed in the field of ultrasonic waves, can be controlled. The chemical processes originating in the ultrasonic wave field and their causes are discussed. Acceleration or inhibition of albumen decomposition processes was found possible through the addition of some organic substances to the solution exposed to the effect of ultrasonic waves. The presence of CCl4 in the albumen solution exposed to ultrasonic waves and its effect on the accumulation of reducing substances is explained. Nine references; 8-USSR and 1-USA (1943-1954). Table; graphs.

Institution: Academy of Sciences USSR, Institute of Biological Physics

Presented by: Academician A. I. Oparin, June 28, 1954

Variable M-841, 26 Oct 11

ELPINER TIE USSR/ Biology - Biochemistry Pub. 22 - 23/40 Card 1/1 : Oparin, A.I., Academician.; Bardinekaya, M.S.; and El'piner, I.E. Authors THE PROPERTY AND PROPERTY OF THE PARTY OF TH Effect of ultrasonic waves on yeast invertase Title Periodical : Dok, AN SSSR 99/3, 423-426, Nov 21, 1954 The change in the activity of a ferment, after being exponed to ultrasonic Abstract waves in an aquous medium and in the presence of methyl a cohol, was investigated. Experimental data obtained indicate that the effect of ultrasonic waves on the invertage is connected first of all ad h the reaction of the ferment with the products of water molecule cleavage. The effect of polymannan contents in the albumin-carbohydrate complex of the invertage, on the stability of the ferment, is elucidated. Ten references: 3-USA; 6-USSR and 1-Swiss (1950-1954). Diagrams. : Academy of Sciences USSR, The A.N. Bakh Institute of Biochemistry and the Institute of Biological Physics June 22, 1954

L'FINER, I. Ye.

"Mechanism Governing the Biological Action of Ultrasonic Waves".

Institute of Biophysics, Academy of Sciences USSR

A report delivered at a conference on Electro-acoustics held by the Acoustic Commission, the Acoustic Institute of the Academy of Sciences USER, and Folytechnic Inst., from 1-5 July 1955 in Kiev.

SO: Sum 728, 28 Nov 1955

Effect of ultrasonic waves on the milk factor. Vop.onk. 1
no.2:42-44 '55. (MLRA 8:10)

1. Is laboratorii eksperimental noy onkologii (sav. chl.korr.
AMN SSSR prof. L.M.Shabad) Akademii meditsinekikh nauk SSSR)
(ULTRASONICS, effects,
on milk factor)
(MEOPLASMS, experimental,
milk factor, eff. of ultrasonics)
(BREAST, neoplasms,
milk factor, eff. of ultrasonics)

ELPINER. 1. 70.

MEDVEDEVA, G.A.; BL!PINER, I.Ye.

Effect of ultrasonic waves on yeast cells. Zhur.obshch. biol. 16 no.4:315-320 J1-Ag '55. (MLRA 8:11)

1. Institut mikrobiologii, Institut biofiziki AN SSSR.

(ULTRASONIC WAVES, effects,

on yeast.)

(YEAST, effect of radiations,

ultraviolet rays)

EL'PINER, I.Ye. doktor biologicheskikh nauk

Ultrasonic waves in biology. Hanka i zhizn' 22 no.7:14-16 Jl '55.

(Ultrasonic waves)

(MLRA 8:9)